(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

CORRECTED VERSION

10/532627

(19) World Intellectual Property Organization International Bureau



I BERKE KANSON NEBOKO HENDERAN BERKERAN EKON KANSON HANDER KANSON KERELANDI KANSON BERKAN HERE KANSON KANSON K

(43) International Publication Date 6 May 2004 (06.05.2004)

PCT

(10) International Publication Number WO 2004/037712 A3

(51) International Patent Classification7: B81B 7/00, 3/00

(21) International Application Number:

PCT/CA2003/001602

(22) International Filing Date: 27 October 2003 (27.10.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 60/421,088

25 October 2002 (25.10.2002)

(71) Applicant (for all designated States except US): MICRO-BRIDGE TECHNOLOGIES INC. [CA/CA]; Suite 202, 1980 Sherbrooke Street West, Montréal, Québec H3H 1E8 (CA).

(72) Inventors; and

- (75) Inventors/Applicants (for US only): LANDSBERGER, Leslie, M. [CA/CA]; 310 Elm Avenue, Westmount, Québec H3Z 1Z5 (CA). GRUDIN, Oleg [CA/CA]; Apt. 2404, 1411 du Fort Street, Montréal, Québec H3H 2N7 (CA).
- (74) Agent: OGILVY RENAULT; Suite 1600, 1981 McGill College Avenue, Montreal, Québec H3A 2Y3 (CA).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


Published:

with international search report

- (88) Date of publication of the international search report: 26 August 2004
- (48) Date of publication of this corrected version: 14 October 2004
- (15) Information about Correction: see PCT Gazette No. 42/2004 of 14 October 2004, Section II

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

METHOD FOR PRODUCING A PACKAGED INTEGRATED CIRCUIT WITH A MICROCAVITY (54) Title



(57) Abstract: There is described a method for producing a packaged integrated circuit. The method comprises a first step of building an integrated circuit having a micro-structure suspended above a micro-cavity, and having a heating element on the micro-structure capable of heating itself and its immediate surroundings. A layer of protective material is then deposited on said micro-structure such that at least a top surface of the micro-structure and an opening of the micro-cavity is covered, wherein the protective material is in a solid state at room temperature and can protect the micro-structure during silicon wafer dicing procedures and subsequent packaging. The integrated circuit is packaged and an electric current is passed through the heating element such that a portion of the protective material is removed and an unobstructed volume is provided above and below the micro-structure.

WO 2004/037712